

STETRON PRODUCT GUIDE

Whether your application calls for the right Loudspeaker, Microphone, Dynamic Receiver or a Full Box Solution, we have the experience and knowledge to support you from concept through to production.

Product	Features	Applications
 <p>Micro-Speakers 10mm - 30mm</p>	<ul style="list-style-type: none"> ▶ Ultra - slim profile ▶ Compound Cone designs ▶ Low THD ▶ High SPL ▶ Round, rectangular and oval form factors 	<ul style="list-style-type: none"> ▶ Mobile devices ▶ Wearables ▶ PNDs (GPS) ▶ Notebook computers ▶ Connected home
 <p>Mid Size Speakers 36mm - 57mm</p>	<ul style="list-style-type: none"> ▶ Low profile ▶ Wide band and narrow band ▶ Low THD ▶ High SPL ▶ Round, rectangular and oval form factors 	<ul style="list-style-type: none"> ▶ Telephony ▶ BT sound box ▶ Tablets ▶ BT car kits ▶ GPS ▶ Multi Media
 <p>Telecom Speakers/Receivers</p>	<ul style="list-style-type: none"> ▶ Up to 18kV ESD Tolerance ▶ Rigid Quality Standards ▶ Flat Frequency Response ▶ Low THD ▶ Wide band and narrow band 	<ul style="list-style-type: none"> ▶ Telephony ▶ Conference units ▶ Laptop Computers ▶ Intercom ▶ Instrumentation ▶ Multi Media
 <p>Commercial Sound</p>	<ul style="list-style-type: none"> ▶ Very Rugged Design ▶ Smooth Response Wide Frequency Range ▶ Low Resonance Frequency 	<ul style="list-style-type: none"> ▶ PA / Background Music / Paging ▶ Residential / Business Medical / Municipal ▶ Commercial Audio OEM's ▶ Sound Masking ▶ Multi Media

CONTACT US TODAY
CUSTOMER SERVICE: U.S.A: 1-800-925-3002 CANADA: 1-877-716-0751
CONTACT@STETRON.COM



WWW.STETRON.COM



Product	Features	Applications
 <p>High Temp, Waterproof Speakers and Microphones</p>	<ul style="list-style-type: none"> ▶ High Temperature per NFPA ▶ Waterproof ▶ Low Distortion ▶ High SPL Output (Speakers) ▶ High SPL Input (Microphones) ▶ High SNR (Microphones) 	<ul style="list-style-type: none"> ▶ Respiratory Protection ▶ Extreme High Temperature Applications
 <p>Fire Alarm/ Evacuation Speakers 2" to 4"</p>	<ul style="list-style-type: none"> ▶ UL1480(2005) ▶ ULC ▶ UL217 520Hz Smoke alarm Standard ▶ High Output, Flat Response, and Low Distortion ▶ Extensively Tested, Qualified for UL & ULC Component Compliance 	<ul style="list-style-type: none"> ▶ Indoor ▶ Outdoor
 <p>Customized Enclosure Systems</p>	<ul style="list-style-type: none"> ▶ Woofer ▶ Tweeter ▶ Passive Radiator ▶ Mid Range ▶ 3D print or CNC prototyping 	<ul style="list-style-type: none"> ▶ Any application requiring an enclosure for a loudspeaker.
 <p>Electret Microphones 4mm - 10mm</p>	<ul style="list-style-type: none"> ▶ Omni / Uni Directional and Noise Cancelling ▶ SMT, Pin and Wire type ▶ High sensitivity and SNR ▶ Waterproof to IPX 8 ▶ High Input SPL 	<ul style="list-style-type: none"> ▶ Telephony ▶ Wearables ▶ BT car kits ▶ GPS ▶ Mobile devices ▶ Fire and safety ▶ Multi Media
 <p>Dynamic Receivers 29mm - 40mm</p>	<ul style="list-style-type: none"> ▶ Low profile ▶ Wide band and narrow band per TIA ▶ Low THD ▶ High SPL ▶ Encapsulated ▶ HAC compatible 	<ul style="list-style-type: none"> ▶ Telephony ▶ Headsets ▶ Gaming ▶ Hearing impaired devices

CONTACT US TODAY
CUSTOMER SERVICE: U.S.A: 1-800-925-3002 CANADA: 1-877-716-0751
CONTACT@STETRON.COM



WWW.STETRON.COM

